



# Fitting Instructions

DETACHABLE TOWBAR DT134Q  
For NISSAN QASHQAI  
2007-

## MATERIALS

|    |   |  |
|----|---|--|
| A  | 1 | Cross Bar  |
| D  | 4 | M12 x 40 x 1.75 Bolts, 2 Nyloc Nuts, 2 off Lock Washers and 6 off 30mm O.D Flat Washers. |
| E  | 5 | M10 x 40 x 1.5 Bolts, 2 Nyloc Nuts, 3 off Lock Washers and 7 off 25mm O.D Flat Washers.  |
| F  | 1 | Right hand angle cleat.  |
| G  | 1 | Left hand chassis stiffener.   |
| H  | 4 | M12 Bolt Caps  |
| J  | 1 | Right hand nut insert (single nut).  |
| K  | 1 | Right hand nut insert (two nuts).  |
| EP | 1 | Electrical Plate (ZEP3)  |
| SC | 1 | Safety Chain Bracket (ZEQ2)  |
| ZQ | 1 | Detachable Neck (ZQ2005)   |

## FITTING

1. Remove bumper (remove clips along lower edge, clips around wheel arch, 1 tip screw and pull back wheel arch extensions to reveal push in clips. Carefully pull bumper backwards to release from clips on rear panel and disconnect reversing sensors (single plug) and fog lamp).
2. Remove chassis end caps (3 bolts) and insert Left hand chassis stiffener (G) inside chassis, loosely attach Crossbar (A) to Stiffener (G) using Bolts (D) with Flat washers. Loosely attach Stiffener (G) to vehicle chassis using remaining Bolts (D).
3. Insert Nut straps (J) and (K) inside right hand chassis openings and loosely attach Crossbar (A) to vehicle chassis using Bolts (E). Loosely attach Angle cleat (F) to chassis and Cross Bar (A) using remaining Bolts (E). Refit chassis end caps.
4. Fully tighten all bolts.
5. Refit bumper.
6. Please refer to ZQ fitting instruction for attachment of Detachable Unit (ZQ), fit Safety Chain Bracket (SC) and Electrical Plate (EP) with Bolts in ZQ kit. Fully tighten all bolts and Fit Bolt Caps (H).

**Note:** This towbar must be used with either a Witter Towball (part number Z11) or Class A50-1 or A50-X towball dimensionally conforming to A50-1 with a 'D' and 'S' value greater than or equal to that of the towbar.

Please refer to the vehicle specification for the trailer weight and nose limits, which **must be observed**.

**Recommended torque settings:** M8 - 27Nm, M10 - 53 Nm, M12 - 95 Nm, M16 - 214 Nm

**Grade 10.9:** M12 – 139Nm, M10 – 78Nm

